



Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:info@chinawheelloaders.com

Tel:0086-532-66739792

Fax:0086-532-66739791

Specification of ZL10 wheel loader



Performance and characteristic

- I、 Streamlined appearance, beautiful and elegant.
- II、 Fully hydraulic steering system, easier operation.
- III、 Bucket can be leveled automatically, high productivity.
- IV 、 Comfortable operation environment, new design cabin, air-conditioner at option.
- V、 Various working devices of attachment are available, such as wooden fork, pipe fork, grass fork, stone bucket, enlarged bucket, plow, fork etc, to meet different needs.



Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:info@chinawheelloaders.com

Tel:0086-532-66739792

Fax:0086-532-66739791



WWW.CHINAWHEELLOADERS.COM



Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

Tel:0086-532-66739792

E-mail:info@chinawheelloaders.com

Fax:0086-532-66739791





Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:info@chinawheelloaders.com

Tel:0086-532-66739792

Fax:0086-532-66739791





Qingdao Zongjin Engineering Machinery Co.,Ltd.

ADD: #1115, International Business Center , NO.196 Zhengyang Rd , Chengyang , Qingdao , China

<http://www.chinawheelloaders.com>

E-mail:info@chinawheelloaders.com

Tel:0086-532-66739792

Fax:0086-532-66739791

Specification	Overall Weight(Kg)	2850
	LxWxH(Mm)	4750x1500x2530
	Rated Bucket Capacity(M³)	0.5
	Rated Load(Kg)	1000
	Wheel Base	1985mm
	Track Base	1215mm
	Max.Breakout Force	22KN
	Maximum Dump Height (Mm)	2300mm
	Reach Fully Raised	850mm
	Bucket Width	1400mm
	Bucket Indicator	Yes
	Engine	Model
Rated Power(Kw)		37KW
Rated Speed(R/Min)		2200
Type		In-Line Arrangement, Water Cooled, Three-Cycle Diesel Engine
Engine Starting Mode		Electric
Brake Mode	Four-Wheel Hydraulic Spread-Shoed Brake	
Steering System	Type	Articulated And Hydraulic Steering
	Min Turning Radius(Mm)	4200
	Min.Ground Clearance	250mm
Tyres	Standard Tyres	1200-16
	Optional Tyres	14/90-16